

FORDEX PTY LTD

142 Fitzgerald Road, Laverton North,
 Victoria Australia 3026.
 Phone 61 3 9369 3455. Fax 61 3 9360 0876



TRADEPAINTS ACRYLIC FENCE FINISH

Exterior – Hard wearing – Outstanding durability.

DESCRIPTION

TradePaints **Fence Finish** is a durable acrylic paint designed for one-coat application to rough sawn or smooth timber fences, outdoor furniture and other timber surfaces.

When applied according to our directions, it imparts a rich lasting colour, which will not rub off when dry.

SURFACE PREPARATION

Remove dust and grime from the surface to be coated.

No priming is necessary although in hot dry weather the surface may be pre-dampened with water to aid penetration.

APPLICATION

Stir thoroughly with a flat-bladed or other paint stirrer.

To ensure one-coat coverage, apply liberally with brush, roller or spray.

No thinning is required for standard applications.

THINNING AND CLEAN UP

Although not normally required or recommended, product may be thinned sparingly with clean water only - additional coats may be required when thinned product is used.

Wash equipment with water immediately after use.

COVERAGE

Spread rate approximately 12 -14 sq. metres per litre.

DRYING

30 minutes at 20°C

If recoating, allow 3 hours between coats - longer at temperatures below 20°C.



Do not apply during periods of extreme heat or humidity, or at temperatures below 10°C.

COLOURS

Charcoal, Mission Brown, Redwood, Indian Red, Brunswick Green, Sage, Cream, White.

CAUTIONS

Provide adequate ventilation in enclosed areas during application and until fully dried.

	Pack size: 10 Lt., 4 Lt.				 Quality Endorsed Company <small>ISO 9001 LIC 2001 Standard Australia</small>
	COVER	CLEAN UP	DRY TIME	RECOAT	
12-14 sq. mt/Lt.	Water	30 minutes @ 20°C	3 hours @ 20°C		
TradePaints is a Trademark of Fordex Pty. Ltd. ACN 075 269 448			Issued June 2008		