



**TRADEPAINTS PAVING PAINT**  
**Interior exterior – Quick drying – Hard wearing.**

**DESCRIPTION**

A quick drying, hard wearing floor and paving paint suitable for use on new and previously painted concrete or wooden floors and paths, driveways, steps, patios, etc.

**SURFACE PREPARATION**

***New unpainted surfaces -***

Ensure that all oil and grease are removed by thorough washing with Mineral Turps and then wipe clean.

On smooth, shiny concrete, first roughen surface to enable proper adhesion by either sanding with abrasive paper or washing with a mixture of 1 part spirits of salts to 20 parts water. After washing down, thoroughly rinse surface with clean water to remove all traces of spirits of salts and allow to dry.

NOTE: Spirits of salts is an acid – take proper precautions when using.

***Previously painted surfaces –***

Remove all loose and flaking paint by either sanding or scraping, making sure to feather the edge with sandpaper to achieve a smooth surface. Remove all traces of polish, wax or any contaminants by washing with mineral turps and wiping clean.

Clean surfaces by washing with warm water and detergent, then rinse thoroughly and allow to dry.

**APPLICATION**

Stir thoroughly with a flat bladed stirrer or other paint stirrer before use.

May be applied by brush, roller or spray equipment.

Apply liberally, painting small sections at a time, brushing back towards previously painted sections.

NOTE – work towards a suitable exit point. Two coats of paving paint are recommended for best appearance and durability.

**THINNING AND CLEAN UP**

Thinning of Trade Paints **Paving Paint** is not recommended.

Wash brushes and other equipment with Mineral Turps immediately after use.

**COVERAGE**

Spread rate approximately 14 sq. metres per litre per coat.

**DRYING**

Within 6 hours at 20°C – longer in cold or humid conditions.

Allow 24 hours between coats - longer at temperatures below 20°C.

Do not apply at temperatures below 10°C



**COLOURS**

Poplar Green, Golden Amber, Bronze Olive, Russet Brown, Ferric Red, Silver Grey, Sandstone, Lino Blue, Terracotta, Mission Brown, Lino Brown, Mist Green, Cherry Red, Light Grey.

**CAUTIONS**

Flammable liquid – keep away from sources of ignition and naked flames. No smoking.

Provide adequate ventilation during application and until fully dried.

	<b>Pack size:</b> 10 Litre, 4 Litre, 1 Litre.				
	<b>COVER</b>	<b>CLEAN UP</b>	<b>DRY TIME</b>	<b>RECOAT</b>	
	14 sq. mt/Lt.	Mineral Turps.	6 hours @ 20°C	24 hours @ 20°C	
Trade Paints is a Trademark of Fordex Pty. Ltd. ACN 075 269 448				Issued June 2008	