

FORDEX PTY LTD

142 Fitzgerald Road, Laverton North,
 Victoria Australia 3026.
 Phone 61 3 9369 3455. Fax 61 3 9360 0876



TRADEPAINTS PAVING SEALER

Exterior – Acrylic solution – Excellent durability.

DESCRIPTION

A high quality, oil based roof and structural finish paint, specially formulated for the protection of all types of steel and galvanised surfaces including roofs, guttering, downpipes, gates, trim, etc.

SURFACE PREPARATION

Disconnect rainwater tanks prior to any preparation work and leave disconnected until drying completed.

Remove dust, grease and dirt by washing down with Mineral Turps. All loose, flaking or peeling paint must be removed by either scraping or wire brush. Clean and dust surface thoroughly.

Galvanised iron – Apply one coat of Trade Paints **Galvanised Iron Primer**; allow to dry for 2 hours before finishing within 48 hours.

Iron or Steel – If free from rust, apply one coat of Trade Paints **Metal Primer** allowing 24 hours before finishing.

If rust is present, remove by wire brushing and then applying a suitable rust remover/converter before priming with Trade Paints **Metal Primer** allowing 24 hours before finishing.

APPLICATION

Stir thoroughly with a flat bladed stirrer or other paint stirrer before use.

May be applied by brush, roller or spray equipment. Apply two coats of Trade Paints **Roof Paint** to achieve the best durability and appearance.

THINNING AND CLEAN UP

Although not normally required, Trade Paints **Roof Paint** may be thinned sparingly with Mineral Turps. Wash brushes and other equipment with Mineral Turps immediately after use.

COVERAGE

Spread rate approximately 14 - 16 sq. metres per litre per coat.

DRYING

6 – 8 hours at 20°C – longer in cold or humid conditions.

Allow 24 hours between coats - longer at temperatures below 20°C.

Do not apply at temperatures below 10°C


COLOURS


Clear

CAUTIONS

Flammable liquid – keep away from sources of ignition and naked flames. No smoking.

Provide adequate ventilation during application and until fully dried.

	Pack size: 4 Lt., 1 Lt.			
	COVER	CLEAN UP	DRY TIME	RECOAT
	14 - 16 sq. mt/Lt.	Mineral Turps.	6 - 8 hours @ 20°C	24 hours @ 20°C
Trade Paints is a Trademark of Fordex Pty. Ltd. ACN 075 269 448				Issued 2008



Quality System
Quality Endorsed Company
ISO 9001:2008