



**DUXSON ACRYLIC SATIN**  
**Exterior – Interior. Walls – Timber – Masonry. Scrubbable.**

**DESCRIPTION**

Duxson **Acrylic Satin** is a premium quality, acrylic based satin paint ideal for use in wet areas such as bathrooms, and laundries. Duxson **Acrylic Satin** is also suitable for use on exterior masonry, brick, render and cement sheet surfaces.

**SURFACE PREPARATION**

Remove dust, dirt and grease with Duxson **Sugar Soap**, mould with Duxson **Mould Wash**, then rinse with clean water and allow to dry before proceeding. Loose flaking paint must be scraped or sanded off to ensure a firm surface. Glossy surfaces must be sanded to a dull finish. Both of these should then be sealed with Duxson **Acrylic Sealer Undercoat**. Fill holes and cracks with suitable filler and sand lightly. Spot prime these repairs with Duxson **Acrylic Sealer Undercoat**.

When painting bare paper covered plasterboard or Hard Set Plaster, it is necessary to apply 1 coat of Duxson **Acrylic Sealer Undercoat**.

No undercoat is necessary when painting interior brick, cement render, stone or fibre cement, however the sealing and filling properties of Duxson **Acrylic Sealer Undercoat** will result in improved appearance and better washability if a coat of this product is used first.

Bare timber must be undercoated with Duxson **Undercoat** prior to application.

**APPLICATION**

Stir thoroughly with a flat bladed or other suitable paint stirrer. Duxson **Acrylic Satin** is supplied ready to use and thinning is not recommended except on porous surfaces such as cement sheet, where up to 100 ml water per litre of paint can be added to ease the application of the first coat. Apply two (2) full coats by brush, roller or spray equipment.

**THINNING AND CLEAN UP**

Thin with clean water if required for painting on absorbent surfaces, or to suit spray application. Wash brushes and other equipment with clean water immediately after use.

**COVERAGE**

Spread rate approximately 14 to 16 sq. metres per litre per coat.

**DRYING**



Touch dry in approx. 1 hour @ 20°C. Allow 3 hours before recoating - for colder or humid conditions, longer times can be expected. Do not apply at temperatures below 10°C, or when likely to fall below 10°C during drying period. Do not apply on exterior surfaces during rainy weather or when rain is expected within 6 hours.

**COLOURS**

White plus a wide range of tinted colours.

**CAUTIONS**

Provide adequate ventilation in enclosed areas during application and until fully dried.

	<b>Pack size:</b> 20 Litre, 10 Litre, 4 Litre, 2 Litre, 1 Litre.				
	<b>COVER</b>	<b>CLEAN UP</b>	<b>DRY TIME</b>	<b>RECOAT</b>	
	14-16 sq. mt/Lt.	Water	1 hour @ 20°C	3 hours @ 20°C	
Duxson Paints is a Trademark of Fordex Pty. Ltd. ACN 075 269 448				Issued June 2008	