

FORDEX PTY LTD

142 Fitzgerald Road, Laverton North,
 Victoria Australia 3026.
 Phone 61 3 9369 3455. Fax 61 3 9360 0876



DUXSON ACRYLIC SEALER UNDERCOAT

Interior - Exterior. Fast drying. Easy application.

DESCRIPTION

Duxson **Acrylic Sealer Undercoat** is an acrylic based undercoat with high covering power, excellent adhesion and good filling properties. It is suitable for both interior and exterior applications when finished with an appropriate top coat.

SURFACE PREPARATION

May be used inside on all unpainted surfaces, especially recommended for cement render, brick, cement sheet and plasterboard. Previously painted surfaces should be sanded smooth.

Exterior timber and metalwork must be primed with appropriate primers prior to application of Duxson **Acrylic Sealer Undercoat**.

Remove dust, dirt and grease with Duxson **Sugar Soap**, mould with Duxson **Mould Wash**, then rinse with clean water and allow to dry before proceeding. Loose flaking paint must be scraped or sanded off to ensure a firm surface. Glossy surfaces must be sanded to a dull finish.

Fill holes and cracks with suitable filler and sand lightly. Spot prime these repairs with Duxson **Acrylic Sealer Undercoat** before undercoating the whole job.

APPLICATION

Stir thoroughly with a flat bladed or other suitable paint stirrer. Apply one full coat by brush, roller or spray equipment and allow to dry.

THINNING AND CLEAN UP

Duxson **Acrylic Sealer Undercoat** is supplied ready to use and thinning is not recommended except on porous surfaces such as cement sheet, where up to 100 ml water per litre of paint can be added to ease the application of the first coat. Apply one full coat by brush, roller or spray equipment and allow to dry. Wash brushes and other equipment with water immediately after use.

COVERAGE

Spread rate approximately 12 to 14 sq. metres per litre per coat.

DRYING



Touch dry in approx. 1 hour @ 20°C. Allow 4 hours before applying finishing coats - for colder or humid conditions, longer times can be expected. Do not apply during periods of extreme heat or at temperatures below 10°C. Do not apply during rainy weather or when rain is expected within 6 hours.

COLOURS

Duxson **Acrylic Sealer Undercoat** may be tinted to a range of pastel shades.

CAUTIONS

Provide adequate ventilation in enclosed areas during application and until fully dried.

	Pack size: 20 Litre, 10 Litre, 4 Litre, 2 Litre, 1 Litre.				
	COVER	CLEAN UP	DRY TIME	RECOAT	
	Duxson Paints is a Trademark of Fordex Pty. Ltd. ACN 075 269 448				

MSDS Ref: ACT 505.2