



DUXSON ACRYLIC WOOD PRIMER
Exterior. Timber.

DESCRIPTION

Duxson **Acrylic Wood Primer** is a specially formulated primer for use on new or burnt-off timber. It combines the application advantages of a water based paint, the durability of a pure acrylic, plus the added benefit of sealing back sap stains. Can be used as a primer under Duxson **Acrylic Gloss**, Duxson **Timbertone Low Sheen** or Duxson **Gloss Enamel**.

SURFACE PREPARATION

Make sure that the surface to be painted is clean, dry and free from dust, dirt and grease.

Exterior timber, which has been exposed to the weather for more than 4 weeks, should be sanded to remove degraded surface fibres.

Fill holes and cracks with a suitable filler and sand lightly. Spot prime these areas with Duxson **Acrylic Wood Primer** before priming the whole surface.

On previously painted surfaces, loose flaky paint must be scraped or sanded off to ensure a firm surface. Only those areas that have been returned to bare timber require priming with this product.

APPLICATION

Stir well with a flat bladed or other suitable paint stirrer.

Apply by brush, roller or spray equipment. Brushing is preferred because it assists penetration and adhesion of the primer.

THINNING AND CLEAN UP

Duxson **Acrylic Wood Primer** is supplied ready to use thinning is not recommended. Up to 2½% water can be added to ease spray application.

Wash brushes and other equipment with clean water immediately after use.

COVERAGE

Spread rate approximately 12 to 14 sq. metres per litre per coat.

DRYING

Touch dry in approx 1hour @20°C. Allow 4 hours before recoating - for colder or humid conditions, longer times can be expected. Do not apply during periods of extreme heat or at temperatures below 10°C. Do not apply during rainy weather or when rain is expected within 6 hours.

COLOURS

Off white

CAUTIONS

Provide adequate ventilation in enclosed areas during application and until fully dried.

	Pack size: 10 Litre, 4 Litre, 1 Litre				
	COVER	CLEAN UP	DRY TIME	RECOAT	
	12-14 sq. mt/Lt.	Water	1 hour @ 20°C	4 hours @ 20°C	
Duxson Paints is a Trademark of Fordex Pty. Ltd. ACN 075 269 448				Issued June 2008	