



DUXSON CEILING WHITE
Interior. Ceilings.

DESCRIPTION

Duxson **Ceiling White** is a premium quality, ultra flat, acrylic based, paint formulated specially for use on ceilings where, if no colour change is involved it's high covering power enables an excellent finish to be obtained with only one coat - for ceilings in wet, steamy areas, Duxson **Acrylic Low Sheen** is recommended. Duxson **Ceiling White** is also suitable for use as a wall paint where washability is not a requirement. The ultra flat finish of Duxson **Ceiling White** makes it ideal for use on surfaces with minor imperfections, which may be accentuated when coated with low sheen paints.

SURFACE PREPARATION

Remove dust, dirt and grease with Duxson **Sugar Soap**, mould with Duxson **Mould Wash**, then rinse with clean water and allow to dry before proceeding. Loose flaking paint must be scraped or sanded off to ensure a firm surface. Glossy surfaces must be sanded to a dull finish. Both of these should then be sealed with Duxson **Acrylic Sealer Undercoat**. Fill holes and cracks with suitable filler and sand lightly. Spot prime these repairs with Duxson **Acrylic Sealer Undercoat**.

When painting bare paper covered plasterboard, it is desirable to apply 1 coat Duxson **Acrylic Sealer Undercoat**.

APPLICATION

Stir well with a flat bladed or other suitable paint stirrer.

Apply one or two coats as required, using paint roller or spray equipment. One coat is usually sufficient when painting previously painted white ceilings.

THINNING AND CLEAN UP

Duxson **Ceiling White** is supplied ready to use and thinning is not recommended except on porous surfaces such as cement sheet, where up to 100 ml water per litre of paint can be added to ease the application of the first coat.

Wash brushes and other equipment with clean water immediately after use.

COVERAGE

Spread rate approximately 14 to 16 sq. metres per litre per coat.

DRYING

Touch dry in approx. 30 minutes @ 20°C. Allow 4 hours before recoating if required - for colder or humid conditions, longer times can be expected.

COLOURS

White

CAUTIONS

Provide adequate ventilation in enclosed areas during application and until fully dried.

	Pack size: 20 Litre, 10 Litre, 4 Litre, 2 Litre, 1 Litre				 Quality Endorsed Company <small>ISO 9001 LIC 38811 Standard Australia</small>
	COVER	CLEAN UP	DRY TIME	RECOAT	
	14 - 16 sq. mt/Lt.	Water	30 minutes @ 20°C	4 hours @ 20°C	
Duxson Paints is a Trademark of Fordex Pty. Ltd. ACN 075 269 448				Issued June 2008	