



DUXSON INTERIOR LOW SHEEN ACRYLIC
Interior. Walls. Washable.

DESCRIPTION

Duxson **Interior Low Sheen Acrylic** is a premium quality, hard wearing, easy to clean, acrylic based paint, which dries to a smooth velvet finish suitable for all interior walls and ceilings - Duxson **Ceiling White** may be used where a flat finish is desired and in wet and steamy areas Duxson **Acrylic Satin** is preferred. On timber surfaces such as doors, cupboards, furniture and architraves, use Duxson **Satin Enamel** or Duxson **Gloss Enamel**.

SURFACE PREPARATION

Remove dust, dirt and grease with Duxson **Sugar Soap**, mould with Duxson **Mould Wash**, then rinse with clean water and allow it to dry before proceeding.

Loose flaking paint must be scraped or sanded off to ensure a firm surface. Glossy surfaces must be sanded to a dull finish.

Fill holes and cracks with suitable filler and sand lightly. Spot prime these repairs with Duxson **Acrylic Sealer Undercoat**.

When painting bare paper covered plasterboard or Hard Set Plaster, it is desirable to first apply 1 coat of Duxson **Acrylic Sealer Undercoat**.

No undercoat is necessary when painting interior brick, cement render, stone or fibre cement, however the sealing and filling properties of Duxson **Acrylic Sealer Undercoat** will result in improved appearance and better washability if a coat of this product is used first.

APPLICATION

Stir well with a flat bladed or other suitable paint stirrer.

Apply 2 full coats by brush, roller or spray equipment.

THINNING AND CLEAN UP

Thinning is normally not recommended except on porous surfaces such as cement sheet where up to 100 ml water per litre of paint can be added to ease the application of the first coat.

Wash up brushes and other equipment with clean water immediately after use. Clean up drips and splashes before they dry and harden using a rag moistened with water.

COVERAGE

Spread rate of approximately 14 – 16 sq. metres per litre per coat.

DRYING


Touch dry in 30 minutes @ 20°C. Allow 3 hours between coats - for colder or more humid conditions, longer times can be expected. Do not apply at temperatures below 10°C, or when likely to fall below 10°C during drying period.

COLOURS

Available in white plus a range of tints.

CAUTIONS

Provide adequate ventilation in enclosed areas during application and until fully dried.

	Pack size: 20 Litre, 10 Litre, 4 Litre, 2 Litre, 1 Litre.			
	COVER	CLEAN UP	DRY TIME	RECOAT
	14 - 16 sq. mt/Lt.	Water	30 minutes @ 20°C	3 hours @ 20°C
Duxson Paints is a Trademark of Fordex Pty. Ltd. ACN 075 269 448				Issued June 2008

