

**FORDEX PTY LTD**

142 Fitzgerald Road, Laverton North,  
 Victoria Australia 3026.  
 Phone 61 3 9369 3455. Fax 61 3 9360 0876



## DUXSON OIL WOOD PRIMER

**Exterior. Timber.**

**DESCRIPTION**

Duxson **Oil Wood Primer** is a lead free primer, specially formulated for use under exterior enamel finishes. Duxson **Oil Wood Primer** is suitable for use on all new or old unpainted timber surfaces.

**SURFACE PREPARATION**

Remove dust, dirt, mould and grease with Duxson **Sugar Soap**, detergent or Duxson **Mould Wash**, rinse with clean water, and allow to dry before proceeding.

Timber, which has been exposed to the weather for more than 4 weeks, should be sanded to remove degraded surface fibres.

Loose flaking paint must be scraped or sanded off to ensure a firm surface.

Fill holes and cracks with suitable filler and sand lightly. Spot prime these repairs with Duxson™ **Oil Wood Primer** before priming the whole surface.

**APPLICATION**

Stir well with a flat bladed or other suitable paint stirrer. Duxson **Oil Wood Primer** is best applied by brush but can be sprayed.

**THINNING AND CLEAN UP**

Duxson **Oil Wood Primer** is supplied ready to use and thinning is not recommended unless application is by spray. Up to 100 ml Mineral Turps per litre of paint can be added to ease spray application.

Wash brushes and other equipment with Mineral Turps immediately after use.

**COVERAGE**

Spread rate approximately 12 to 14 sq. metres per litre per coat but may be lower on porous open grained timber and some plywoods.

**DRYING**



Touch dry in approx 6 hours @ 20°C. Allow 24 hours before recoating - for colder or humid conditions, longer times can be expected. Do not apply at temperatures below 10°C.

**COLOURS**

Pink

**CAUTIONS**

Flammable liquid – keep away from sources of ignition and naked flames. No smoking. Provide adequate ventilation in enclosed areas during application and until fully dried.

	<b>Pack size:</b> 10 Litre, 4 Litre, 20 Litre, 1 Litre, 500 ml, 250 ml.				 <b>Quality Endorsed Company</b> <small>ISO 9001 LIC 3891 Standard Australia</small>
	<b>COVER</b>	<b>CLEAN UP</b>	<b>DRY TIME</b>	<b>RECOAT</b>	
	12-14 sq. mt/Lt.	Mineral Turps.	6 hours @ 20°C	24 hours @ 20°C	
Duxson Paints is a Trademark of Fordex Pty. Ltd. ACN 075 269 448				Issued June 2008	

MSDS Ref: ACT 508.2