

FORDEX PTY LTD

142 Fitzgerald Road, Laverton North,
 Victoria Australia 3026.
 Phone 61 3 9369 3455. Fax 61 3 9360 0876



DUXSON POLYURETHANE

Interior. Timber.

DESCRIPTION

Duxson **Polyurethane** finishes are premium quality, hard wearing, clear polyurethane based coatings available as gloss, satin and matt. They are not recommended for exterior use. For additional toughness, Duxson **High Wear Additive** may be added. For timber floors, Tradepaints **Polyurethane Floor Coating** is recommended.

SURFACE PREPARATION

Timber must be clean, dry and free from contamination. To ensure best adhesion, timber should be freshly sanded just prior to finishing. Previously sealed, or painted surfaces should be sanded back to bare timber or, if in good condition, sanded smooth and a small test area painted and allowed to dry to check adhesion between the coats. Fill nail holes, cracks and blemishes with a synthetic timber putty coloured to match the timber. If the timber requires colouring, an Interior Stain suited to the type of timber should be applied and dried according to product instructions.

APPLICATION

Stir Duxson **Polyurethane** thoroughly with a flat bladed paint stirrer before use and occasionally during use. Apply using a good quality brush or lambswool applicator. Cut in along edges first using a good brush well filled with paint. Apply two to three coats sanding lightly in the direction of the grain between coats.

THINNING & CLEAN UP

Duxson **Polyurethane** is supplied ready for use and thinning is not recommended unless application is by spray. Up to 100 ml Mineral Turps per litre of paint may be required to enable spray application. Clean up all equipment with mineral turpentine. Clean up drips and splashes before they dry and harden using a rag moistened with mineral turpentine.

COVERAGE:

Spread rate approximately 14 to 16 sq. metres per litre per coat.

DRYING:



Touch dry in approx. 6 hours @ 20°C. Allow 24 hours before recoating - for colder or humid conditions, longer times can be expected. Do not apply at temperatures below 10°C or when likely to fall below 10°C during the drying period.

COLOURS:

Clear only

CAUTIONS

Ensure plenty of fresh air. Only paint in well ventilated areas. Keep out of the reach of children. Ensure all sources of ignition such as pilot lights and other naked flames are extinguished before starting to paint. Do not smoke while painting. Replace lid securely after painting. Store upside down in a cool dry place.

	Pack size: 10 Litre, 4 Lt, 1 Litre, 500 MI, 250 MI.				 Quality Endorsed Company <small>ISO 9001:2008 STANDARDS AUSTRALIA</small>
	COVER	CLEAN UP	DRY TIME	RECOAT	
	14 -16 sq. mt/Lt.	Mineral Turpentine	6 hours @ 20°C	24 hours @ 20°C	
Duxson Paints is a Trademark of Fordex Pty. Ltd. ACN 075 269 448				Issued June 2008	

MSDS Ref: ACT 512.2