



DUXSON TIMBERTONE LOW SHEEN
Exterior - Interior. Timber - Masonry.

DESCRIPTION

Duxson **Timbertone Low Sheen** is a premium quality, long life, exterior acrylic based paint that dries quickly to a soft low sheen finish on exterior timber and masonry (brick, cement sheet, and render) surfaces without the need for a separate primer coat. Can also be used for interior trim, where it can be overcoated with Duxson **Polyurethane** for a hard wearing finish.

SURFACE PREPARATION

Remove dust, dirt and grease with Duxson **Sugar Soap**, mould with Duxson **Mould Wash**, then rinse with clean water and allow to dry before proceeding. Loose flaking paint must be scraped or sanded off to ensure a firm surface. Glossy surfaces must be sanded to a dull finish. Bare timber areas should be spot primed with Duxson **Acrylic Wood Primer**. Fill holes and cracks with suitable filler and sand lightly. Spot prime these repairs with Duxson **Timbertone Low Sheen**. Repairs on masonry surfaces should be spot primed with Duxson **Acrylic Sealer Undercoat** or Duxson **Timbertone Low Sheen**.

No undercoat is necessary when painting interior brick, cement render, stone or fibre cement, however the sealing and filling properties of Duxson **Acrylic Sealer Undercoat** will result in improved appearance and better washability if a coat of this product is used first

APPLICATION

Stir well with a flat bladed or other suitable paint stirrer.

Apply 2 full coats by brush, roller or spray equipment.

THINNING AND CLEAN UP

Thinning is not recommended except on porous surfaces such as cement sheet where up to 100 ml water per litre of paint can be added to ease the application of the first coat.

Wash up brushes and other equipment with clean water immediately after use. Clean up drips and splashes before they dry and harden using a rag moistened with water.

COVERAGE

Spread rate approximately 14 to 16 sq. metres per litre per coat.

DRYING

Touch dry in 60 minutes @ 20°C. Allow 4 hours between coats - for colder or more humid conditions, longer times can be expected. Do not apply at temperatures below 10°C, or when likely to fall below 10°C during drying period.

COLOURS

Available in white plus a wide range of tinted colours.

CAUTIONS

Provide adequate ventilation in enclosed areas during application and until fully dried.

	Pack size: 10 Litre, 4 Litre, 1 Litre.				
	COVER	CLEAN UP	DRY TIME	RECOAT	
	14 - 16 sq. mt/Lt.	Water	60 minutes @ 20°C	4 hours @ 20°C	
Duxson Paints is a Trademark of Fordex Pty. Ltd. ACN 075 269 448				Issued June 2008	