



DUXSON UNDERCOAT
Interior-exterior – Timber - Metals.

DESCRIPTION

Duxson **Undercoat** is a premium quality lead-free undercoat especially for use under enamel finishes. It has been formulated to provide excellent exterior durability on timber when used as a system with Duxson **Pink Primer** and Duxson **Gloss Enamel** and is ideal for interior applications such as bare timber or previously painted surfaces.

SURFACE PREPARATION

May be used inside on most unpainted surfaces. Use Duxson **Acrylic Sealer Undercoat** on new Plaster, Plasterboard and Cement Rendered surfaces.

Exterior bare surfaces must be primed with appropriate primers prior to application of Duxson **Undercoat**.

Remove dust, dirt and grease with Duxson **Sugar Soap**, mould with Duxson **Mould Wash**, then rinse with clean water and allow it to dry before proceeding.

Previously painted surfaces should be sanded smooth. Loose flaky paint must be scraped or sanded off to ensure a firm surface. Glossy surfaces must be sanded to a dull finish.

Fill holes and cracks with suitable filler and sand lightly. Spot prime these repairs with Duxson **Undercoat**, before undercoating the whole project surface.

APPLICATION

Stir thoroughly with a flat bladed or other suitable paint stirrer.

Apply one full coat, sand and dust down well for applying top coat.

THINNING AND CLEAN UP

Thinning is not recommended unless application is by spray. Up to 100 ml Mineral Turps per litre of paint can be added to ease spray application.

Wash brushes and other equipment with Mineral Turps immediately after use.

COVERAGE

Spread rate approximately 12 to 14 sq. metres per litre per coat.

DRYING

Touch dry in approx. 6 hrs @ 20°C. Allow 24 hours before recoating – for colder or humid conditions, longer times can be expected. Do not apply at temperatures below 10°C, or likely to fall below 10°C during drying period.


COLOURS

Duxson™ **Undercoat** may be tinted to a range of pastel shades.

CAUTIONS

Flammable liquid – keep away from sources of ignition and naked flames. No smoking.

Provide adequate ventilation in enclosed areas during application and until fully dried.

	Pack size: 10 Litre, 4 Lt, 2 Litre, 1 Litre, 500 ML, 250 ML.			
	COVER	CLEAN UP	DRY TIME	RECOAT
	12-14 sq. mt/Lt.	Mineral Turps.	6 hours @ 20°C	24 hours @ 20°C
Duxson Paints is a Trademark of Fordex Pty. Ltd. ACN 075 269 448			Issued June 2008	

